



Environmental Monitoring Solutions

Evaporimeter



- Class A evaporation pan design acconding to WMO
- Evaporation derived calculation using LSI LASTEM's acquisition systems
- Automatic water refill system
- High accuracy and resolution piezometric water level sensor
- Stainless steel assembling

LSI-LASTEM evaporimeter pan and platform are built to WMO standards for class "A" evaporimeters. The pan is made in stainless steel. The platform is made of white plastic. The pan features a stainless steel still well fit to contain the evaporimeter level sensor. The sensor consists of a piezometric water level sensor with analogue output for easy connection to any data acquisition systems. LSI LASTEM data loggers can manage the switching of a solenoid valve for the automatic refill of water (when the measured level is below 25 cm).

PN	DYI010	
Evaporation pan	Design	WMO Class A
	Housing	Stainless steel AISI 304
	Evaporation surface	1.143 m ²
	Steel well	Included Ø 120 mm, H. 280 mm
	Weight	22 kg
	Dimensions	Ø 1207 mm; H. 254 mm
	Water discharge level	214 mm
	Pan thickness	Frame: 2 mm

Technical Specifications

Accessories

DYI013	Plastic made platform
DQC102	Piezometric type water level sensor
	Range: 0200 mm
	Output: 420 mA (RS485 Mobus-RTU: using MDMMA1010.1 unit
	Accuracy: • Linearity: 0,1 % FS • Stability: 0,1% FS • Hysteresis: 0,03% FS
	Resolution: 0.1 mm
	Weight: 2 kg





		Temp. Coeff Zero: typical: 0.015% FS/K, Max: 0.02% FS/K
		Temp. Coeff sensitivity: typical: 0.01% FS/K, Max: 0.02% FS/K
		Material: Stainless steel
		Operative temperature: 050 °C
		Power supply: 12 V DC, Power consumption< 4 mA
		Data Logger compatiblity: E-Log
	DWA510A	Cable L=10 m
	DWA525A	Cable L=25 m
	DWA526A	Cable L=50 m
	DWA527A	Cable L=100 m
	DYI012	Pan water top-up system, 12 V DC. Weight: 0.45 kg



LSI LASTEM Srl Via Ex SP. 161 Dosso, 9 20049 Settala (MI) Italy Tel. +39 02 954141 Fax +39 02 95770594 Email info@lsi-lastem.com www.lsi-lastem.com

